Aquatic Mammals 2020, *46*(5), 444-453, DOI 10.1578/AM.46.5.2020.444

Temporary Hearing Threshold Shift at Ecologically Relevant Frequencies in a Harbor Porpoise (*Phocoena phocoena*) Due to Exposure to a Noise Band Centered at 88.4 kHz

Ronald A. Kastelein,[1] Lean Helder-Hoek,[1] Suzanne A. Cornelisse,[1]
Léonie A. E. Huijser,[1] and Robin Gransier[2]

[1]*Sea Mammal Research Company (SEAMARCO), Julianalaan 46, 3843 CC Harderwijk, The Netherlands*
E-mail: researchteam@zonnet.nl
[2]*KU Leuven – University of Leuven, Department of Neurosciences,*
ExpORL, Herestraat 49 Bus 721, B-3000 Leuven, Belgium

Abstract

Susceptibility to temporary hearing threshold shift (TTS) in harbor porpoises (*Phocoena phocoena*) depends on the frequency of the fatiguing sound causing the shift. TTS in harbor porpoises has been tested for sounds within the 1 to 63 kHz frequency range. Susceptibility to TTS caused by sounds of ~88 kHz is ecologically relevant since these sounds are expected to affect hearing in the frequency range of harbor porpoise echolocation signals. TTS was quantified in a female porpoise after exposure for 1 h to a continuous one-sixth-octave noise band centered at 88.4 kHz, at average received sound pressure levels of 137 to 161 dB re 1 µPa (resulting sound exposure levels [SELs]: 173 to 197 dB re 1 µPa^{2}s). To quantify TTS and recovery, hearing thresholds for 88.4, 100, and 125 kHz tonal signals were determined before and after exposure. Control trials were used as a baseline and to determine which exposure levels resulted in statistically significant TTS in the 4 min after the fatiguing sound stopped (TTS$_{1-4}$). At 88.4 kHz, the lowest SEL that resulted in significant TTS$_{1-4}$ (3.6 dB) was 185 dB re 1µPa^{2}s; at 100 kHz, the lowest SEL that resulted in significant TTS$_{1-4}$ (5.2 dB) was 191 dB re 1 µPa^{2}s; and at 125 kHz, the lowest SEL that resulted in significant TTS$_{1-4}$ (5.4 dB) was 191 dB re 1 µPa^{2}s. At higher SELs, the TTS at this frequency remained similar. The highest TTS$_{1-4}$ (13.1 dB) occurred at 100 kHz after exposure to an SEL of 197 dB re 1 µPa^{2}s. In most cases, hearing recovered within 12 min after the fatiguing sound stopped; in the remaining cases, recovery took less than 1 h. TTS onset (defined as 6 dB TTS; Southall et al., 2019) occurred after exposures to SELs of ~191 dB re 1 µPa^{2}s (when hearing was measured at 100 kHz, one third of an octave above the center frequency of the fatiguing sound).

Key Words: anthropogenic noise, audiogram, frequency weighting, harbor porpoise, *Phocoena phocoena*, hearing, hearing damage, hearing loss, hearing sensitivity, odontocete, temporary threshold shift, TTS

Introduction

The harbor porpoise (*Phocoena phocoena*) is of particular interest when studying the effects of anthropogenic underwater sound on marine mammals, as this odontocete species not only has a wide distribution area in the coastal waters of the northern hemisphere (Bjorge & Tolley, 2008) but also possesses acute hearing (i.e., low hearing thresholds) in a wide frequency range (Kastelein et al., 2017b). The harbor porpoise appears to be particularly susceptible to temporary hearing threshold shifts (TTSs) caused by fatiguing sounds (e.g., from vessel traffic, pile driving, seismic surveys, detonations, and sonar), as TTS onset occurs at lower sound exposure levels (SELs) in the harbor porpoise than in the other odontocete species that have been tested (Finneran, 2015; Tougaard et al., 2016; Houser et al., 2017).

Depending on exposure parameters, sound-induced TTSs vary in magnitude and duration, and have the potential to compromise feeding, orientation, communication, and predator detection in wild harbor porpoises and other marine mammals that mainly rely on acoustics for these life functions (e.g., Au, 1993). Therefore, TTSs may negatively impact individual health, reproduction, and survival, even if permanent hearing threshold shift does not occur. In the long term, TTSs could have adverse population effects.

As susceptibility to TTS depends not only on the fatiguing sound's received sound pressure level (SPL) and the exposure duration but also on the sound's frequency (see Finneran, 2015), it is important to quantify the effect of various fatiguing sound frequencies on the hearing of the harbor porpoise (National Marine Fisheries Service [NMFS], 2016; Houser et al., 2017). For the regulation of underwater acoustic levels in areas where harbor porpoises occur, complete equal-TTS susceptibility contours are desirable, covering the entire frequency range of hearing in the harbor porpoise (i.e., 0.5 to 140 kHz). Within the 1 to 63 kHz range, an equal-TTS susceptibility contour for the following nine frequencies has been established: (1) 1.5 kHz, (2) 1 to 2 kHz, (3) 4 kHz, (4) 3.5 to 4.1 kHz, (5) 6 to 7 kHz, (6) 6.5 kHz, (7) 16, (8) 32, and (9) 63 kHz (Kastelein et al., 2012, 2013, 2014a, 2014b, 2015b, 2017a, 2019a, 2019b, 2020a, 2020b). However, susceptibility to TTS in the harbor porpoise has not been assessed in the frequency range that includes the peak frequency of its echolocation (~125 kHz; Møhl & Andersen, 1973). Once quantification of susceptibility to TTS over the entire hearing range is complete, it will be possible to model a research-based auditory weighting curve for harbor porpoises and other odontocetes that echolocate at high frequencies (Southall et al., 2019). Weighting is applied to measured sound levels in an attempt to account for the relative susceptibility to TTS of an animal, as the ear's susceptibility to TTS varies with frequency within the hearing range.

The present study builds upon our previous TTS research by investigating the susceptibility to TTS of harbor porpoises after exposure to fatiguing sounds centered at 88.4 kHz. In odontocetes, TTS usually occurs half an octave above the frequency of the narrow-band fatiguing sound (Popov et al., 2011, 2013; Finneran, 2015; Kastelein et al., 2014b, 2019a, 2019b, 2020a, 2020b), so fatiguing sounds of 88.4 kHz are expected to affect hearing at the peak frequency of echolocation clicks produced by the harbor porpoise (~125 kHz; Møhl & Andersen, 1973). Sounds with frequencies in the 88.4 kHz range include biological sounds such as echolocation signals of bottlenose dolphins (*Tursiops truncatus*; Au, 1993) and anthropogenic sounds such as some types of fish-finding sonars (range: 20 to 200 kHz; Discovery of Sound In The Sea [DOSITS], 2019). TTS and the rate of hearing recovery were quantified as functions of SEL and hearing test frequency in a female harbor porpoise after exposure to a one-sixth-octave noise band (NB) centered at 88.4 kHz. The goal was to increase the frequency range for which an equal-TTS susceptibility contour for harbor porpoises can be generated (see Houser et al., 2017) to improve their regulatory protection.

Methods

Study Animal and Site

The study animal, a previously stranded and rehabilitated adult female harbor porpoise (identified as F05; age: ~8 y old, body mass: ~41 kg, body length: 154 cm, and girth at axilla: ~79 cm), had participated in previous studies of TTS induced by sounds of 3.5 to 4.1, 16, 32, and 63 kHz (Kastelein et al., 2017a, 2019a, 2019b, 2020a). These previous studies did not compromise her auditory ability, and her hearing thresholds in the frequency range tested in the present study (88.4 to 125 kHz) are representative of those of similar-aged harbor porpoises (Kastelein et al., 2017b).

The study was conducted at the SEAMARCO Research Institute, the Netherlands. The harbor porpoise was kept in a quiet pool complex designed and built for acoustic research, consisting of an outdoor pool (12 m × 8 m; 2 m deep) connected via a channel (4 m × 3 m; 1.4 m deep) to an indoor pool (8 m × 7 m; 2 m deep). For details of the pool, equipment, and water flow, see Kastelein et al. (2019b).

Acoustics

SPL Measurement Equipment and Ambient Noise—Acoustical terminology follows ISO 18405:2017 (International Organization for Standardization [ISO], 2017). The ambient noise was measured, and the fatiguing sound and hearing test signals were calibrated every 3 mo during the study period (for calibration methods, see Kastelein et al., 2019b). Under test conditions (i.e., water circulation system off, no rain, and Beaufort wind force 4 or below), the ambient noise in the indoor pool was very low; the one-third-octave level increased from 55 dB re 1 µPa at 200 Hz to 60 dB re 1 µPa at 5 kHz. This was similar to the level at which previous TTS studies with harbor porpoises had been conducted (see Kastelein et al., 2012, 2013, 2014a, 2014b, 2015a, 2015b, 2017a, 2019a, 2019b, 2020a, 2020b).

Fatiguing Sound—The digitized fatiguing sound was produced, transmitted, calibrated, and checked before each exposure session, as described by Kastelein et al. (2019b). The fatiguing sound consisted of a continuous (duty cycle 100%) one-sixth-octave Gaussian white noise band (NB), centered at 88.4 kHz (bandwidth: 78.8 to 99.2 kHz). Ideally, a 88.4 kHz tone would have been used, but in a pool, a pure tone can lead to a very heterogeneous sound field due to reverberation. Therefore, instead of a tonal signal, a very narrow NB was used. The center frequency was selected based on previous TTS studies (e.g., Popov et al., 2011, 2013; Finneran, 2015; Kastelein et al., 2014b, 2019a, 2019b, 2020a, 2020b) in which the highest TTS occurred half an octave above the center frequency of the fatiguing sound. Half an octave above 88.4 kHz is ~125 kHz, which, for harbor porpoises, is in the range of most sensitive hearing (Kastelein et al., 2017b); it also is the peak frequency of their echolocation (Møhl & Andersen, 1973).

To determine the fatiguing sound's distribution in the outdoor pool, the SPL of the NB was measured at 76 locations in the horizontal plane (on a horizontal grid of 1 m × 1 m), and at three depths per location on the grid (0.5, 1.0, and 1.5 m below the surface), resulting in a total of 228 measurements in the pool (Figure 1). Differences in mean SPL per depth (based on the power sum) were minimal (e.g., 144 ± 3 dB at 0.5 m, 144 ± 2 dB at 1.0 m, and 143 ± 1 dB at 1.5 m deep; Figures 1a, b & c, respectively). In the example shown in Figure 1, the average SPL of all 228 measurements based on the power sum was 144 ± 2 dB re 1 µPa.

0.5 m

7	**141**	**142**	**143**	**144**	**144**	**143**	**144**	**144**	**143**	**142**	**141**	
6	**141**	**143**	**142**	**145**	**146**	**145**	**146**	**145**	**142**	**143**	**141**	
5	**142**	**142**	**143**	**146**	148	149	148	**146**	**143**	**142**	**142**	
4	**142**	**144**	**144**	**147**	152		152	**147**	**144**	**144**	**142**	
3	**139**	**141**	**142**	**146**	143	148	143	**146**	**142**	**141**	**139**	
2	**140**	**142**	**144**	**143**	**143**	**144**	**143**	**143**	**144**	**142**	**140**	
1	**139**	**140**	**142**	**143**	**143**	**141**	**143**	**143**	**142**	**140**	**139**	
	1	**2**	**3**	**4**	**5**	**6**	**7**	**8**	**9**	**10**	**11**	

a)

1.0 m

7	**141**	**142**	**143**	**144**	**145**	**144**	**145**	**144**	**143**	**142**	**141**	
6	**141**	**143**	**142**	**145**	**146**	**145**	**146**	**145**	**142**	**143**	**141**	
5	**141**	**143**	**141**	**144**	148	149	148	**144**	**141**	**143**	**141**	
4	**143**	**142**	**145**	**142**	145	**T**	145	**142**	**145**	**142**	**143**	
3	**142**	**142**	**143**	**145**	145	148	145	**145**	**143**	**142**	**142**	
2	**142**	**143**	**142**	**143**	**144**	**143**	**144**	**143**	**142**	**143**	**142**	
1	**141**	**142**	**142**	**143**	**144**	**143**	**144**	**143**	**142**	**142**	**141**	
	1	**2**	**3**	**4**	**5**	**6**	**7**	**8**	**9**	**10**	**11**	

b)

1.5 m

7	**140**	**142**	**142**	**143**	**143**	**144**	**143**	**143**	**142**	**142**	**140**	
6	**142**	**143**	**143**	**144**	**144**	**144**	**144**	**144**	**143**	**143**	**142**	
5	**142**	**143**	**142**	**142**	143	143	143	**142**	**142**	**143**	**142**	
4	**142**	**143**	**144**	**142**	140		140	**142**	**144**	**143**	**142**	
3	**142**	**142**	**143**	**144**	143	143	143	**144**	**143**	**142**	**142**	
2	**141**	**143**	**143**	**142**	**143**	**145**	**143**	**142**	**143**	**143**	**141**	
1	**141**	**141**	**142**	**143**	**142**	**144**	**142**	**143**	**142**	**141**	**141**	
	1	**2**	**3**	**4**	**5**	**6**	**7**	**8**	**9**	**10**	**11**	

c)

Figure 1. An example of the SPL distribution in the outdoor pool used by the harbor porpoise (*Phocoena phocoena*) during exposure to the continuous (100% duty cycle) one-sixth-octave noise band (NB) centered at 88.4 kHz (the fatiguing sound), measured at depths of 0.5 m (a), 1.0 m (b), and 1.5 m (c). T = location of the transducer, which was placed at 1 m depth in the center of the pool (source level: 152 dB re 1 µPa). The numbers in the grey fields indicate 1 m markings on the side of the pool. In this example, the mean SPL for the entire pool is 144 ± 2 dB re 1 µPa (*n* = 228). During the exposure sessions, the porpoise avoided the area adjacent to the transducer in the center of the pool. Therefore, the mean SPL in the area used by the porpoise during sound exposure (bold numbers) is 143 ± 2 dB re 1 µPa (*n* = 204).

To determine the average SPL received by the harbor porpoise, the area where she swam during exposure periods was quantified following the methods of Kastelein et al. (2019b). During all exposure periods, the porpoise avoided the area within ~1.5 m of the transducer, which was in the center of the pool at 1 m depth. Therefore, measurements from this area were excluded, and the SPL she was exposed to was calculated as the mean of the SPL measurements in the area where she swam (mean exposure was 143 dB ± 2 dB re 1 µPa based on 204 measurements; Figure 1). Thus, exposure for 1 h resulted in an SEL of 179 dB re 1 µPa^{2}s.

Hearing Test Signals—Linear upsweep tonal sounds with a duration of 1 s (and 50 ms on and off ramps) were used as the psychophysical hearing test signals that the harbor porpoise was asked to detect before and after exposure to the fatiguing sound (see Kastelein et al., 2019b). The center frequencies of the sweeps tested were 88.4 kHz (the center frequency of the fatiguing sound), 100 kHz (an arbitrary intermediate frequency), and 125 kHz (half an octave higher than the center frequency). We did not test at higher frequencies, as harbor porpoise hearing sensitivity declines rapidly above 130 kHz (Kastelein et al., 2017b). The hearing test signals were generated digitally, and were calibrated and checked daily, as explained by Kastelein et al. (2019b).

Experimental Procedures

One total sound exposure test, consisting of (1) a pre-exposure hearing test starting at ~0830 h, (2) fatiguing sound exposure (or control period) for 1 h (although expressed in hours in this manuscript, the exposure periods were exactly 60 min, timed with stopwatches) in the morning or early afternoon, and (3) a number of post-sound exposure hearing tests in the afternoon, was conducted per day. All hearing tests were performed in the indoor pool. During the 1-h fatiguing sound exposure, the harbor porpoise was in the outdoor pool. Data were collected from February to October 2018, following the protocol developed and explained by Kastelein et al. (2019b).

The harbor porpoise was always tested immediately after the fatiguing sound stopped. Her hearing thresholds were measured during post-sound exposure (PSE) periods 1-4 min ($PSE_{1\text{-}4}$), 4-8 min ($PSE_{4\text{-}8}$), 8-12 min ($PSE_{8\text{-}12}$), and, if hearing had not recovered within 12 min, 60 min (PSE_{60}) after the sound exposure had ended. Hearing was considered to have recovered when the hearing threshold was less than 2 dB above the pre-exposure threshold level. The SPLs of the fatiguing sound were tested in random order (six fatiguing sound SPLs for hearing test sound frequency 88.4 kHz, three SPLs for 100 kHz, and six SPLs for 125 kHz with a resulting SEL range of 173 to 197 dB re 1 µPa^{2}s). Each SEL was tested at least four times per hearing frequency. Exceptions to this were the lowest SELs, which caused less than 2 dB TTS, and the highest SEL (197 dB), testing of which was limited due to animal welfare considerations (for those SELs, only two tests were conducted per frequency compared to four or five tests for most other frequency-SPL combinations; for sample sizes, see the "Results" section).

Control tests were conducted in the same way and under the same conditions as sound exposure tests, but without the fatiguing sound exposure. Each control test started with a pre-exposure hearing test session and was followed by exposure to the normal ambient noise in the outdoor pool for 1 h with all the equipment installed. The transducer was placed in the pool as usual but did not emit sound. Post-ambient exposure (PAE; control) hearing test sessions were then performed 1-4 min ($PAE_{1\text{-}4}$), 4-8 min ($PAE_{4\text{-}8}$), and 8-12 min ($PAE_{8\text{-}12}$) after the ambient noise exposure period ended. At least four control tests were conducted per hearing test frequency, and they were randomly dispersed among the fatiguing sound exposure tests; on each test day, either a sound exposure test or a control test was conducted.

Hearing Test Procedures

A hearing test trial began with the harbor porpoise at the start/response buoy. Following a hand signal by her trainer, she swam to the listening station. The porpoise stationed there for a random period of between 6 and 12 s before the signal operator produced the test signal (in signal-present trials). She then either swam back to the start/response buoy to indicate that she had heard the signal or stayed at the listening station if she had not heard the signal. About two thirds of each session consisted of signal-present trials and about one third consisted of signal-absent (catch) trials (during which the trainer used a whistle after between 6 and 12 s to instruct the porpoise to return to the start/response buoy where she received a food reward). After a correct response to a signal-present trial, the porpoise went to the start/response buoy and received a food reward. After an incorrect response to a signal-present trial, the porpoise was asked to return to the start/response buoy, and no food reward was given. A switch from a test signal level to which the porpoise responded to a level to which she did not respond, or vice versa, was called a "reversal." Each complete hearing test session consisted of ~25 trials and lasted for up to 12 min (subdivided into three

4-min periods in the first PSE or PAE session). During pre-exposure and PSE_{60} hearing test sessions, the goal was to obtain 10 reversals. During each of the 4-min periods within the first PSE and PAE sessions, the goal was to obtain a minimum of three reversals. If this goal was not met, the session was not used for analysis. The methodology is described in more detail by Kastelein et al. (2019b).

Data Analysis

When the harbor porpoise returned to the start/response buoy before receiving a test signal (in signal-present trials) or hearing the trainer's whistle (in signal-absent trials), her response was called a "pre-stimulus." The mean pre-stimulus response rate for both signal-present and signal-absent trials was calculated as the number of pre-stimuli as a percentage of all trials in each hearing test period.

The pre-exposure mean 50% hearing threshold ($PE_{50\%}$) for a hearing test sound was determined by calculating the mean SPL of all reversal pairs obtained during the pre-exposure hearing session. TTSs after the sound exposure sessions (TTS_{1-4}, TTS_{4-8}, TTS_{8-12}, and TTS_{60}) were calculated by subtracting $PE_{50\%}$ from the mean 50% hearing thresholds during PSE_{1-4}, PSE_{4-8}, PSE_{8-12}, and PSE_{60} periods of the same day (see Kastelein et al., 2019b). Similarly, the hearing thresholds measured on a control session day were compared by subtracting $PE_{50\%}$ from the mean 50% hearing thresholds obtained during the PAE periods of the same day.

The onset of TTS is commonly defined as occurring at 6 dB (Houser et al., 2017; Southall et al., 2019). We use this definition in the "Discussion," but define the onset of statistically significant TTS as occurring at the lowest SEL at which a statistically significant difference could be detected between the TTS due to the fatiguing sound exposures and the "TTS" as measured after the control exposures (this "shift" was close to zero). The level of significance was established by conducting a separate one-way ANOVA on the mean TTS_{1-4} for each hearing test frequency with the factor SEL (including zero as the control), followed by Dunnett multiple comparisons between the control and the other levels of the factor (Dunnett, 1964). All analyses were conducted using the software *Minitab 18* (Minitab LLC, State College, PA, USA), and data conformed to the underlying assumptions of the tests applied (i.e., homogeneity of variances and normal distribution of residuals; Zar, 1999).

Results

Pre-Stimulus Response Rate

Before and after the 1-h sound exposure periods, the harbor porpoise was always willing to participate in the hearing tests. In ~5% of the sessions, she moved slowly from the outdoor (exposure) pool to the indoor (testing) pool, so the minimum of three reversals could not be obtained in the first time period after the fatiguing sound had stopped (i.e., PSE_{1-4}); data from these sessions were therefore discarded. The mean pre-stimulus response rate for both signal-present and signal-absent trials in the hearing tests varied between 3.8 and 7.7% (Table 1). The pre-stimulus response rates in the pre-exposure, post sound-exposure, and post-ambient exposure (control) periods were similar.

Effect of SEL on TTS

The ANOVAs showed that the TTS_{1-4} was significantly affected by the fatiguing sound's SEL at all three hearing test frequencies. Post-hoc Dunnett multiple comparisons with the controls revealed that the onset of statistically significant TTS occurred at SELs of either 185 or 191 dB re 1 $\mu Pa^2 s$, depending on the hearing test frequency (Table 2; Figure 2).

Table 1. The pre-stimulus response rate by harbor porpoise F05 in hearing tests during the pre-exposure periods, after exposure to the fatiguing sound (a continuous one-sixth-octave noise band centered at 88.4 kHz), and after exposure to ambient noise (control). All exposure levels and the three hearing test frequencies were pooled for the calculation of percentages. Sample sizes (total numbers of hearing trials in all sessions per period) are shown in parentheses.

	Period				
Fatiguing sound	Pre-exposure	PSE_{1-4}	PSE_{4-8}	PSE_{8-12}	PSE_{60}
	6.7% (1,108)	3.8% (339)	6.8% (355)	7.7% (378)	5.8% (138)
Control	Pre-exposure	PAE_{1-4}	PAE_{4-8}	PAE_{8-12}	--
	5.2% (557)	5.7% (193)	6.2% (193)	5.8% (206)	--

Table 2. Results of one-way ANOVAs of mean TTS_{1-4} (in dB) in F05 after exposure for 1 h to the fatiguing sound (a continuous one-sixth-octave noise band centered at 88.4 kHz) with the factor "fatiguing sound exposure level" (SEL). Df = degrees of freedom. Standard deviation (SD) is shown for each mean TTS_{1-4}, as well as the range and sample size (*n*). Mean initial TTSs that were significantly different from the control according to Dunnett multiple comparisons are indicated with an asterisk, and the SELs of the onset of statistically significant TTS are indicated in bold.

Hearing test frequency (kHz)	ANOVA results ($F_{df\,1,\,df\,2}$, *p* value)	SPL (dB re 1 µPa)	SEL (dB re 1 $\mu Pa^2 s$)	TTS_{1-4} (dB)			
				Mean	SD	Range	*n*
88.4	$F_{6,26} = 8.40$ $p < 0.001$	Control	Control	0.8	0.7	-0.1-1.8	9
		137	173	0.7	1.0	-0.4-1.9	4
		143	179	1.8	0.9	0.6-2.7	4
		149	**185**	3.6*	0.5	3.1-4.1	4
		155	191	2.9*	1.1	1.8-4.5	5
		158	194	2.9*	1.3	1.9-4.7	5
		161	197	0.1	1.0	-0.6-0.9	2
100	$F_{3,10} = 129.1$ $p < 0.001$	Control	Control	-0.1	0.7	-1.0-0.6	4
		149	185	-0.1	0.3	-0.4-0.4	4
		155	**191**	5.2*	1.3	3.9-6.9	4
		161	197	13.1*	0.7	12.6-13.6	2
125	$F_{6,24} = 39.14$ $p < 0.001$	Control	Control	0.3	0.8	-1.4-1.3	14
		137	173	-0.3	0.8	-0.8-0.3	2
		143	179	1.8	--	--	1
		149	185	1.6	0.6	1.0-2.4	4
		155	**191**	5.4*	1.2	4.2-6.7	4
		158	194	6.1*	1.5	4.8-7.9	4
		161	197	5.9*	0.2	5.8-6.1	2

For hearing test signals of 88.4 kHz, statistically significant TTS_{1-4} occurred in the harbor porpoise after exposure to an SEL of 185 dB re 1 $\mu Pa^2 s$ (Table 2; Figure 2). Hearing recovered within 60 min even after the greatest TTS_{1-4} measured (3.6 dB; Figure 3a). For hearing test signals of 100 kHz, statistically significant TTS_{1-4} occurred after exposure to an SEL of 191 dB re 1 $\mu Pa^2 s$ (Table 2; Figure 2), and hearing recovered within 60 min even after the greatest TTS_{1-4} (13.1 dB; Figure 3b). For hearing test signals of 125 kHz, statistically significant TTS_{1-4} occurred after exposure to an SEL of 191 dB re 1 $\mu Pa^2 s$ (Figure 2), and hearing recovered within 12 min, even after the greatest TTS_{1-4} (6.1 dB; Figure 3c). As expected, the control sessions showed that the hearing thresholds for all three hearing test signal frequencies before and after 1-h exposures to the low ambient noise were very similar (Table 2; Figure 3).

2013), Yangtze finless porpoises (*Neophocaena phocaenoides asiaeorientalis*; Popov et al., 2011), and belugas (*Delphinapterus leucas*; Popov et al., 2013). Finneran & Schlundt (2013) found greater susceptibility to TTS in bottlenose dolphins for fatiguing sound frequencies between 10 and 30 kHz than for 80 kHz. Popov et al. (2011) showed that susceptibility to TTS in the Yangtze finless porpoise, a species more closely related to the harbor porpoise, is also frequency dependent: susceptibility decreased with increasing fatiguing sound frequency (i.e., 32, 45, 64, and 128 kHz). A similar effect was found for belugas, which are more susceptible to TTS for fatiguing sound frequencies 11.2 and 22.5 kHz than for 45 and 90 kHz (Popov et al., 2013). Corresponding to the trend observed in these previous studies, the present study suggests that the onset of TTS (defined as 6 dB TTS) in harbor porpoises that have been exposed to sounds of 88.4 kHz occurs at higher SELs (191 dB re 1 μPa^2s; hearing measured at 100 kHz, which is one third of an octave above the center frequency of the fatiguing sound) than after exposure to sounds of 4, 6.5, 16, and 32 kHz (Kastelein et al., 2012, 2014a, 2019a, 2019b, 2020b, present study; Figure 4). The next step in quantifying susceptibility to TTS over the entire hearing range will be to test one more fatiguing sound frequency: 0.5 kHz. Completion of this step will allow an auditory weighting curve to be modeled for the harbor porpoise.

Acknowledgments

We thank research assistant Naomi Claeys; students Tessa Kreeft, Cosmin Parlog, Lin Hopmans, Emmy Post, and Joshi van Berlo; and volunteers Stacey van der Linden, Femke Bucx, Lotte Dalmeijer, Kimberly Biemond, and Brigitte Slingerland for their help in collecting the data. We thank Arie Smink for the design, construction, and maintenance of the electronic equipment. We thank Bert Meijering (Topsy Baits) for providing space for the SEAMARCO Research Institute. Erwin Jansen (TNO) conducted the acoustic measurements. We also thank Nancy Jennings (Dotmoth.co.uk), Maria Morell (University of Veterinary Medicine Hannover), and two anonymous reviewers for their valuable constructive comments on this manuscript. Nancy Jennings also conducted the statistical analysis. Funding for this project was obtained from the U.S. Navy, Living Marine Resources program (Contract No. N39430-15-C-1686). We thank Anu Kumar and Mandy Shoemaker for their guidance on behalf of the LMR program. The harbor porpoise was tested under authorization of the Netherlands Ministry of Economic Affairs with Endangered Species Permit FF/75A/2014/025. We thank the ASPRO group for providing the porpoise.

Literature Cited

Au, W. W. L. (1993). *The sonar of dolphins*. Springer-Verlag.

Bjorge, A., & Tolley, K. A. (2008). Harbor porpoise *Phocoena phocoena*. In W. F. Perrin, B. Würsig, & J. G. M. Thewissen (Eds.), *Encyclopedia of marine mammals* (2nd ed., pp. 530-532). Academic Press.

Davis, R. R., Kozel, P., & Erway, L. C. (2003). Genetic influences in individual susceptibility to noise: A review. *Noise and Health*, *5*(20), 19-28.

Discovery Of Sound In The Sea (DOSITS). (2019). Homepage. https://dosits.org

Dunnett, C. W. (1964). New tables for multiple comparisons with a control. *Biometrics*, *20*(3), 482-491. https://doi.org/10.2307/2528490

Finneran, J. J. (2015). Noise-induced hearing loss in marine mammals: A review of temporary threshold shift studies from 1996-2015. *The Journal of the Acoustical Society of America*, *138*(3), 1702-1726. https://doi.org/10.1121/1.4927418

Finneran, J. J., & Schlundt, C. E. (2013). Effects of fatiguing tone frequency on temporary threshold shift in bottlenose dolphins (*Tursiops truncatus*). *The Journal of the Acoustical Society of America*, *133*(3), 1819-1826. https://doi.org/10.1121/1.4776211

Finneran, J. J., Schlundt, C. E., Dear, R., Carder, D. A., & Ridgway, S. H. (2002). Temporary shift in masked hearing thresholds in odontocetes after exposure to single underwater impulses from a seismic watergun. *The Journal of the Acoustical Society of America*, *111*(6), 2929-2940. https://doi.org/10.1121/1.1479150

Henderson, D., Subramaniam, M., & Boettcher, F. A. (1993). Individual susceptibility to noise-induced hearing loss: An old topic revisited. *Ear and Hearing*, *14*(3), 152-168. https://doi.org/10.1097/00003446-199306000-00002

Henderson, D., Subramaniam, M., Graton, M. A., & Saunders, S. S. (1991). Impact of noise: The importance of level, duration, and repetition rate. *The Journal of the Acoustical Society of America*, *89*(3), 1350-1357. https://doi.org/10.1121/1.400658

Houser, D. S., Yost, W., Burkard, R., Finneran, J. J., Reichmuth, C., & Mulsow, J. (2017). A review of the history, development and application of auditory weighting functions in humans and marine mammals. *The Journal of the Acoustical Society of America*, *141*(3), 1371-1413. https://doi.org/10.1121/1.4976086

International Organization for Standardization (ISO). (2017). *Underwater acoustics – Terminology* (ISO Standard No. 18405:2017). https://www.iso.org/obp/ui/#iso:std:iso:18405:ed

Kastelein, R. A., Helder-Hoek, L., & Van de Voorde, S. (2017a). Effects of exposure to 53-C sonar playback sounds (3.5-4.1 kHz) on harbor porpoise (*Phocoena phocoena*) hearing. *The Journal of the Acoustical Society of America*, *142*(4), 1965-1975. https://doi.org/10.1121/1.5005613

Kastelein, R. A., Helder-Hoek, L., & Van de Voorde, S. (2017b). Hearing thresholds of a male and a female harbor porpoise (*Phocoena phocoena*). *The Journal of* *the Acoustical Society of America*, *142*(2), 1006-1010. https://doi.org/10.1121/1.4997907

Kastelein, R. A., Cornelisse, S. A., Huijser, L. A. E., & Helder-Hoek, L. (2020a). Temporary hearing threshold shift in harbor porpoises (*Phocoena phocoena*) due to one-sixth-octave noise bands at 63 kHz. *Aquatic Mammals*, *46*(2), 167-182. https://doi.org/10.1578/AM.46.2.2020.167

Kastelein, R. A., Gransier, R., Hoek, L., & Olthuis, J. (2012). Temporary threshold shifts and recovery in a harbor porpoise (*Phocoena phocoena*) after octave-band noise at 4 kHz. *The Journal of the Acoustical Society of America*, *132*(5), 3525-3537. https://doi.org/10.1121/1.4757641

Kastelein, R. A., Gransier, R., Hoek, L., & Rambags, M. (2013). Hearing frequency thresholds of a harbor porpoise (*Phocoena phocoena*) temporarily affected by a continuous 1.5 kHz tone. *The Journal of the Acoustical Society of America*, *134*(3), 2286-2292. https://doi.org/10.1121/1.4816405

Kastelein, R. A., Gransier, R., Marijt, M. A. T., & Hoek, L. (2015a). Hearing frequencies of a harbor porpoise (*Phocoena phocoena*) temporarily affected by played back offshore pile driving sounds. *The Journal of the Acoustical Society of America*, *137*(2), 556-564. https://doi.org/10.1121/1.4906261

Kastelein, R. A., Gransier, R., Schop, J., & Hoek, L. (2015b). Effect of intermittent and continuous 6-7 kHz sonar sweep exposures on harbor porpoise (*Phocoena phocoena*) hearing. *The Journal of the Acoustical Society of America*, *137*(4), 1623-1633. https://doi.org/10.1121/1.4916590

Kastelein, R. A., Schop, J., Gransier, R., & Hoek, L. (2014a). Frequency of greatest temporary hearing threshold shift in harbor porpoises (*Phocoena phocoena*) depends on the noise level. *The Journal of the Acoustical Society of America*, *136*(3), 1410-1418. https://doi.org/10.1121/1.4892794

Kastelein, R. A., Helder-Hoek, L., Cornelisse, S. A., Defillet, L. N., & Huijser, L. A. E. (2020b). Temporary threshold shift in a second harbor porpoise (*Phocoena phocoena*) after exposure to a one-sixth-octave noise band at 1.5 kHz and a 6.5 kHz continuous wave. *Aquatic Mammals*, *46*(5), 431-446. https://doi.org/10.1578/AM.46.5.2020.431

Kastelein, R. A., Helder-Hoek, L., Cornelisse, S., Huijser, L. A. E., & Gransier, R. (2019a). Temporary hearing threshold shift in harbor porpoises (*Phocoena phocoena*) due to one-sixth-octave noise band at 32 kHz. *Aquatic Mammals*, *45*(5), 549-562. https://doi.org/10.1578/AM.45.5.2019.549

Kastelein, R. A., Helder-Hoek, L., van Kester, R., Huisman, R., & Gransier, R. (2019b). Temporary hearing threshold shift in harbor porpoises (*Phocoena phocoena*) due to one-sixth-octave noise band at 16 kHz. *Aquatic Mammals*, *45*(3), 280-292. https://doi.org/10.1578/AM.45.3.2019.280

Kastelein, R. A., Hoek, L., Gransier, R., Rambags, M., & Claeys, N. (2014b). Effect of level, duration, and inter-pulse interval of 1-2 kHz sonar signal exposures on harbor porpoise hearing. *The Journal of the Acoustical Society of America*, *136*(1), 412-422. https://doi.org/10.1121/1.4883596

Kryter, K. D., Weisz, A. Z., & Wiener, F. M. (1962). Auditory fatigue from audio analgesia. *The Journal of the Acoustical Society of America*, *34*(3), 484-491. https://doi.org/10.1097/00043764-196209000-00040

Kylin, B. (1960). Temporary threshold shift and auditory trauma following exposure to steady-state noise. *Acta Oto-Laryngology*, Supp. 152, 51-56.

Lucke, K., Siebert, U., Lepper, P. A., & Blanchet, M-A. (2009). Temporary shift in masked hearing thresholds in a harbor porpoise (*Phocoena phocoena*) after exposure to seismic airgun stimuli. *The Journal of the Acoustical Society of America*, *125*(6), 4060-4070. https://doi.org/10.1121/1.3117443

Møhl, B., & Andersen, S. (1973). Echolocation: High-frequency component in the click of the harbour porpoise (*Phocoena ph*. L.). *The Journal of the Acoustical Society of America*, *53*(5), 1368-1372. https://doi.org/10.1121/1.1914435

National Marine Fisheries Service (NMFS). (2016). *Technical guidance for assessing the effects of anthropogenic sound on marine mammal hearing: Underwater acoustic thresholds for onset of permanent and temporary threshold shifts* (NOAA Technical Memorandum NMFS-OPR-55). U.S. Department of Commerce, National Oceanic and Atmospheric Administration. 178 pp.

Popov, V. V., Supin, A. Ya., Wang, D., Wang, K., Dong, L., & Wang, S. (2011). Noise-induced temporary threshold shift and recovery in Yangtze finless porpoise *Neophocaena phocaenoides asiaeorientalis*. *The Journal of the Acoustical Society of America*, *130*(1), 574-584. https://doi.org/10.1121/1.3596470

Popov, V. V., Supin, A. Ya., Rozhnov, V. V., Nechaev, D. I., Sysuyeva, E. V., Klishin, V. O., Pletenko, M. G., & Tarakanov, M. B. (2013). Hearing threshold shifts and recovery after noise exposure in beluga whales, *Delphinapterus leucas*. *Journal of Experimental Biology*, *216*(9), 1587-1596. https://doi.org/10.1242/jeb.078345

Southall, B. L., Finneran, J. J., Reichmuth, C., Nachtigall, P. E., Ketten, D. R., Bowles, A. E., Ellison, W. T., Nowacek, D. P., & Tyack, P. L. (2019). Marine mammal noise exposure criteria: Updated scientific recommendations for residual hearing effects. *Aquatic Mammals*, *45*(2), 125-232. https://doi.org/10.1578/AM.45.2.2019.125

Spankovich, C., Griffiths, S. K., Lobariñas, E., Morgenstein, K. E., de la Calle, S., Ledon, V., Guercio, D., & Le Prell, C. G. (2014). Temporary threshold shift after impulse-noise during video game play: Laboratory data. *International Journal of Audiology*, *53*(2), S53-S65. https://doi.org/10.3109/14992027.2013.865844

Tougaard, J., Wright, A. J., & Madsen, P. T. (2016). Noise exposure criteria for harbor porpoises. In A. N. Popper & A. Hawkins (Eds.), *The effects of noise on aquatic life II: Advances in experimental medicine and biology* (Vol. 875, pp. 1167-1173). Springer Science+Business Media. https://doi.org/10.1007/978-1-4939-2981-8_146

Zar, J. H. (1999). *Biostatistical analysis*. Prentice-Hall. 718 pp.